

High Tech Tubular Frame Instrument Work Center Carts

Model TW - Vibration reducer cart provides safe, mobile instrument work station with high tech tubular appearance

1,200 LB CAPACITY*



Options:

- 2 wheel brakes on swivel casters - **Code BN or B5**
- Conductive drag chain - **Code DC**
- Floor Lock - **Code FN or F5**

Product Features:

- **Top and bottom shelves covered with shock absorbing, non-slip cushioned, non-conductive vinyl matting.**
- **Wrap-around bumper** (top shelf) protects walls and doorways.
- **Lockable drawer** with 2 sets of keys - Drawer Size:
36" Cart - 5"h x 16"w x 20"d
48" Cart - 5"h x 20"w x 20"d
- **6 outlet power strip** with 15 amp circuit breaker and 3 prong grounded 15 ft cord with cord storage.
- Bottom shelf 24" x 26" (TW236) and 24" x 38" (TW248).
- Clearance under drawer - 14".
- All welded construction (except casters and top MDF wood shelf).
- Tubular construction, and 12 gauge caster mounts for long lasting use.
- Tubular handle with smooth radius bend for comfort and uniform appearance.
- Bolt on casters, 2 swivel & 2 rigid, for easy replacement and superior cart tracking - see specifications chart.
- Both shelves flush.
- Overall height - 34" (8" casters), 31" (5" casters).

SPECIFICATIONS

WxL (in)	8" Full Pneumatic Casters Cat. No.	8" Semi Pneumatic Casters Cat. No.	Wgt. (lbs)	5" Casters Cat. No.	
				Polyurethane	Wgt.(lbs)
24 x 36	TW236-N8	TW236-Z8	146	TW236-U5	122
48	TW248-N8	TW248-Z8	166	TW248-U5	142

High Tech Tubular Frame Instrument Transportation Carts

Model TB - Vibration reducer cart provides safe instrument transportation with high tech tubular appearance

1,200 LB CAPACITY*



Options:

- 2 wheel brakes on swivel casters - **Code BN or B5**
- 6 outlet power strip - **Code PS**
- Lockable drawer with 2 keys - Drawer Size:
36" Cart - 5"h x 16"w x 20"d - **Code DS**
48" Cart - 5"h x 20"w x 20"d - **Code DX**
- Conductive drag chain - **Code DC**
- Floor Lock - **Code FN or F5**

Product Features:

- **Top and bottom shelves covered with shock absorbing, non-slip cushioned, non-conductive vinyl matting.**
- **Wrap-around bumper** (top shelf) protects walls and doorways.
- Bottom shelf 24" x 26" (TB236) and 24" x 38" (TB248).
- Clearance between shelves - 21".
- All welded construction (except casters and top MDF wood shelf).
- Tubular corner construction, and 12 gauge caster mounts for long lasting use.
- Tubular handle with smooth radius bend for comfort and uniform appearance.
- Bolt on casters, 2 swivel & 2 rigid, for easy replacement and superior cart tracking - see specifications chart.
- Both shelves flush.
- Overall height - 34" (8" casters), 31" (5" casters).

SPECIFICATIONS

WxL (in)	8" Full Pneumatic Casters Cat. No.	8" Semi Pneumatic Casters Cat. No.	Wgt. (lbs)	5" Casters Cat. No.	
				Polyurethane	Wgt.(lbs)
24 x 36	TB236-N8	TB236-Z8	122	TB236-U5	98
48	TB248-N8	TB248-Z8	142	TB248-U5	118

Angular Frame - Instrument 2 Shelf Carts

Models AB, AE, AL - Vibration reducer carts to safely transport instruments

1,200 LB CAPACITY*



Model AB Shown

1,200 LB CAPACITY*



Model AE Shown

1,200 LB CAPACITY*



Model AL Shown

Product Features:

- Top and bottom shelves covered with shock absorbing, non-slip cushioned, non-conductive vinyl matting.
- All welded construction (except casters), durable 12 gauge steel shelves, 3/16" thick angle corners, and 12 gauge caster mounts for long lasting use.
- Tubular handle with smooth radius bend (Model AE - raised ergonomic style, Model AL - 12" raised offset handle).
- Bolt on casters, 2 swivel & 2 rigid - see specifications chart.
- 1-1/2" shelf lips down (flush) on both shelves (see options).
- Clearance between shelves - 20" (except Model AL - 17").
- Top shelf height - 34" (8" casters), 30" (5" casters) except Model AL - 31" (8" casters), 27" (5" casters)

Options:

- 2 wheel brakes on swivel casters - **Code BN or B5**
- Floor lock - **Code FN or F5**
- Both shelves lips up - **Code GA**
- Locking drawer (16"w x 5"h x 20"d) with 2 keys - **Code DS**
- 6 outlet power strip with 15 amp circuit breaker and 3 prong grounded 15 ft cord with cord storage - **Code PS**
- Conductive drag chain - **Code DC**
- Other top shelf heights available

Model AB - With Standard Level Handle

WxL (in)	8" Full Pneumatic Casters Cat. No.	8" Semi Pneumatic Casters Cat. No.	Wgt. (lbs)	5" Casters Cat. No.	
				Polyurethane	Wgt.(lbs)
18 x 30	AB130-N8	AB130-Z8	114	AB130-U5	88
36	AB136-N8	AB136-Z8	122	AB136-U5	96
24 x 36	AB236-N8	AB236-Z8	130	AB236-U5	106
42	AB242-N8	AB242-Z8	140	AB242-U5	116
48	AB248-N8	AB248-Z8	150	AB248-U5	126
60	AB260-N8	AB260-Z8	172	AB260-U5	146
30 x 36	AB336-N8	AB336-Z8	148	AB336-U5	124
48	AB348-N8	AB348-Z8	174	AB348-U5	150
60	AB360-N8	AB360-Z8	200	AB360-U5	174
36 x 48	AB448-N8	AB448-Z8	198	AB448-U5	172
60	AB460-N8	AB460-Z8	228	AB460-U5	202

Model AE - With Ergonomic Handle

WxL (in)	8" Full Pneumatic Casters Cat. No.	8" Semi Pneumatic Casters Cat. No.	Wgt. (lbs)	5" Casters Cat. No.	
				Polyurethane	Wgt.(lbs)
18 x 30	AE130-N8	AE130-Z8	110	AE130-U5	86
36	AE136-N8	AE136-Z8	120	AE136-U5	96
24 x 36	AE236-N8	AE236-Z8	132	AE236-U5	108
42	AE242-N8	AE242-Z8	142	AE242-U5	118
48	AE248-N8	AE248-Z8	152	AE248-U5	128
60	AE260-N8	AE260-Z8	174	AE260-U5	148
30 x 36	AE336-N8	AE336-Z8	150	AE336-U5	126
48	AE348-N8	AE348-Z8	176	AE348-U5	152
60	AE360-N8	AE360-Z8	202	AE360-U5	176
36 x 48	AE448-N8	AE448-Z8	200	AE448-U5	174
60	AE460-N8	AE460-Z8	230	AE460-U5	204

Model AL - Low Profile With Raised Offset Handle

WxL (in)	8" Full Pneumatic Casters Cat. No.	8" Semi Pneumatic Casters Cat. No.	Wgt. (lbs)	5" Casters Cat. No.	
				Polyurethane	Wgt.(lbs)
18 x 30	AL130-N8	AL130-Z8	116	AL130-U5	90
36	AL136-N8	AL136-Z8	124	AL136-U5	98
24 x 36	AL236-N8	AL236-Z8	132	AL236-U5	108
42	AL242-N8	AL242-Z8	142	AL242-U5	118
48	AL248-N8	AL248-Z8	152	AL248-U5	128
60	AL260-N8	AL260-Z8	174	AL260-U5	148
30 x 36	AL336-N8	AL336-Z8	150	AL336-U5	126
48	AL348-N8	AL348-Z8	176	AL348-U5	152
60	AL360-N8	AL360-Z8	202	AL360-U5	176
36 x 48	AL448-N8	AL448-Z8	200	AL448-U5	174
60	AL460-N8	AL460-Z8	230	AL460-U5	204

Angular Frame - Instrument Low Profile Carts (2 Shelves)

Models AD, AF, AJ - Low Profile vibration reducer carts to safely transport instruments

1,200 LB CAPACITY*



Model AD Shown

1,200 LB CAPACITY*



Model AF Shown

1,200 LB CAPACITY*



Model AJ Shown

Product Features:

- Top and bottom shelves covered with shock absorbing, non-slip cushioned, non-conductive vinyl matting.
- All welded construction (except casters).
- Durable 12 gauge steel shelves, 3/16" thick angle corners, and 12 gauge caster mounts for long lasting use.
- Raised offset handle (12" above top shelf).
- **Locking drawer(s)** (16"w x 5"h x 20"d) with 2 keys except Model AJ.
- **12 gauge door(s)** with locking handle and 2 keys except Model AD.
- Bolt on casters, 2 swivel & 2 rigid, for easy replacement and superior cart tracking - see specifications chart.
- 1-1/2" shelf lips down (flush) on both shelves.
- Clearance between shelves - 17" (under drawer 11" where applicable).
- Top shelf height (Models AD & AJ) - 31" (8" casters), 27" (5" casters).
- Top shelf height (Model AF) - 35" (8" casters), 31" (5" casters).

Options:

- 2 wheel brakes on swivel casters - **Code BN or B5**
- Floor lock - **Code FN or F5**
- 6 outlet power strip with 15 amp circuit breaker and 3 prong grounded 15 ft cord with cord storage - **Code PS**
- Conductive drag chain - **Code DC**
- All shelf lips up (Model AD only) - **Code GA**
- Drawers keyed differently - **Code KS**
- Other top shelf heights available (Model AD only).

Model AD - With 1 Drawer

WxL (in)	8" Full Pneumatic Casters Cat. No.	8" Semi Pneumatic Casters Cat. No.	Wgt. (lbs)	5" Casters Cat. No.	
				Polyurethane	Wgt. (lbs)
24 x 36	AD236-N8	AD236-Z8	154	AD236-U5	130
42	AD242-N8	AD242-Z8	164	AD242-U5	140
48	AD248-N8	AD248-Z8	174	AD248-U5	150
60	AD260-N8	AD260-Z8	196	AD260-U5	170
30 x 36	AD336-N8	AD336-Z8	172	AD336-U5	148
48	AD348-N8	AD348-Z8	198	AD348-U5	174
60	AD360-N8	AD360-Z8	224	AD360-U5	198
36 x 48	AD448-N8	AD448-Z8	222	AD448-U5	196
60	AD460-N8	AD460-Z8	252	AD460-U5	226

Model AF - With 3 Drawers and 1 Door

WxL (in)	8" Full Pneumatic Casters Cat. No.	8" Semi Pneumatic Casters Cat. No.	Wgt. (lbs)	5" Casters Cat. No.	
				Polyurethane	Wgt. (lbs)
24 x 36	AF236-N8	AF236-Z8	236	AF236-U5	210
48	AF248-N8	AF248-Z8	266	AF248-U5	240
30 x 36	AF336-N8	AF336-Z8	260	AF336-U5	236
48	AF348-N8	AF348-Z8	298	AF348-U5	274

Model AJ - With 2 Doors

WxL (in)	8" Full Pneumatic Casters Cat. No.	8" Semi Pneumatic Casters Cat. No.	Wgt. (lbs)	5" Casters Cat. No.	
				Polyurethane	Wgt. (lbs)
24 x 36	AJ236-N8	AJ236-Z8	176	AJ236-U5	150
48	AJ248-N8	AJ248-Z8	206	AJ248-U5	180
30 x 36	AJ336-N8	AJ336-Z8	200	AJ336-U5	176
48	AJ348-N8	AJ348-Z8	238	AJ348-U5	214

Angular Frame - Instrument Transportation Carts (3 Shelves)

Model AC - Large vibration reducer carts to safely transport instruments

1,200 LB CAPACITY*



Options:

- 2 wheel brakes on swivel casters - **Code BN or B5**
- Floor lock - **Code FN or F5**
- Ergonomic handle - **Code EH**
- All shelves lips up for retention - **Code GA**
- 6 outlet power strip with 15 amp circuit breaker and 3 prong grounded 15 ft cord with cord storage - **Code PS**
- Conductive drag chain - **Code DC**
- Other top shelf heights available.

Product Features:

- All shelves covered with shock absorbing, non-slip cushioned, non-conductive vinyl matting.
- All welded construction (except casters).
- Durable 12 gauge steel shelves, 3/16 thick angle corners, and 12 gauge caster mounts for long lasting use.
- Tubular handle with smooth radius bend for comfort and uniform appearance.
- Bolt on casters, 2 swivel & 2 rigid, for easy replacement and superior cart tracking - see specifications chart.
- 1-1/2" shelf lips down (flush) on all shelves (see options).
- Clearance between shelves - 20".
- Overall height - 56" (8" casters), 52" (5" casters).

SPECIFICATIONS

WxL (in)	8" Full Pneumatic Casters Cat. No.	8" Semi Pneumatic Casters Cat. No.	Wgt. (lbs)	5" Casters Cat. No.	
				Polyurethane	Wgt.(lbs)
18 x 36	AC136-N8	AC136-Z8	156	AC136-U5	122
	AC148-N8	AC148-Z8	182	AC148-U5	148
24 x 36	AC236-N8	AC236-Z8	176	AC236-U5	142
	AC242-N8	AC242-Z8	190	AC242-U5	158
48	AC248-N8	AC248-Z8	206	AC248-U5	172
	AC260-N8	AC260-Z8	236	AC260-U5	204
30 x 36	AC336-N8	AC336-Z8	200	AC336-U5	168
	AC348-N8	AC348-Z8	238	AC348-U5	206
60	AC360-N8	AC360-Z8	276	AC360-U5	242
	AC448-N8	AC448-Z8	270	AC448-U5	236
36 x 48	AC460-N8	AC460-Z8	316	AC460-U5	282

Instrument Transfer Cart (2 shelves)

Model AK - Vibration reduction transporter for instruments

1,200 LB CAPACITY*



Options:

- 2 wheel brakes on swivel casters - **Code BN or B5**
- All swivel casters - **Code AS**
- Floor lock - **Code FN or F5**
- Both shelves lips up for retention - **Code GA**
- Vinyl matting on top shelf - **Code VM**
- Tubular push handle - **Code PH**
- Other top shelf heights available

Product Features:

- All shelves covered with shock absorbing, non-slip cushioned, non-conductive vinyl matting.
- All welded construction (except casters).
- Durable **12 gauge steel shelves**, 3/16" thick angle corners, and 12 gauge caster mounts for long lasting use.
- Bolt on casters, 2 swivel & 2 rigid, for easy replacement and superior cart tracking - see specifications chart.
- 1-1/2" shelf lips down (flush) on both shelves (see options).
- Clearance between shelves - 20".
- Overall height - 34" (8" casters), 30" (5" casters).

SPECIFICATIONS

WxL (in)	8" Full Pneumatic Casters Cat. No.	8" Semi Pneumatic Casters Cat. No.	Wgt. (lbs)	5" Casters Cat. No.	
				Polyurethane	Wgt.(lbs)
24 x 30	AK230-N8	AK230-Z8	104	AK230-U5	80
	AK236-N8	AK236-Z8	114	AK236-U5	90
42	AK242-N8	AK242-Z8	124	AK242-U5	100
	AK248-N8	AK248-Z8	134	AK248-U5	110
60	AK260-N8	AK260-Z8	156	AK260-U5	132
	AK272-N8	AK272-Z8	174	AK272-U5	150
30 x 36	AK336-N8	AK336-Z8	130	AK336-U5	106
	AK348-N8	AK348-Z8	154	AK348-U5	130
60	AK360-N8	AK360-Z8	178	AK360-U5	152
	AK372-N8	AK372-Z8	202	AK372-U5	178
36 x 48	AK448-N8	AK448-Z8	174	AK448-U5	150
	AK460-N8	AK460-Z8	202	AK460-U5	178
72	AK472-N8	AK472-Z8	230	AK472-U5	206

Instrument Platform, Ergonomic Platform & Wagon Trucks

Models PA, AY, AG - Heavy duty one level transporters at various heights

1,200 LB CAPACITY*



Model PA Shown

1,200 LB CAPACITY*



Model AY Shown

2,000 LB CAPACITY*



Model AG Shown

Product Features:

- All welded frame construction (except handles & casters).
- 12 gauge steel platform.
- Platform covered with shock absorbing, non-slip cushioned, non-conductive vinyl matting.
- Removable 1-1/4" tubular handle with smooth radius bend mounted into sockets. (Except Model AG - tubular handle with 1" "T handle & rubber grips.)
- Flush platform for easy loading.
- Bolt on casters, 2 swivel & 2 rigid, for easy replacement (except Model AG - wheels) - see specifications chart.

Specific model Features:

Model PA

- Platform height - 12" (8" casters), 8" (5" casters).
- Handle height above deck - 30".

Model AY - Ergonomic Height Platform

- Platform height - 31" (8" casters), 27" (5" casters).
- Handle height above deck - 16".

Model AG

- Platform height - 18" (12" wheels), and 20" (16" wheels).
- Solid rod axles - 3/4".

Options:

- 2 wheel brakes on swivel casters - **Code BN or B5**
- Floor lock (Model PA only) - **Code FN or F5**
- Conductive drag chain - **Code DC**
- Adjustable height option (Model AY only) - 3 positions, fixed height plus or minus 2" - **Code AL**

Model PA - Low Platform

WxL (in)	8" Full Pneumatic Casters Cat. No.	8" Semi Pneumatic Casters Cat. No.	Wgt. (lbs)	5" Casters Cat. No.	
				Polyurethane	Wgt. (lbs)
18 x 36	PA136-N8	PA136-Z8	86	PA136-U5	64
	PA148-N8	PA148-Z8	92	PA148-U5	70
24 x 36	PA236-N8	PA236-Z8	94	PA236-U5	72
	PA242-N8	PA242-Z8	100	PA242-U5	78
48	PA248-N8	PA248-Z8	106	PA248-U5	84
	PA260-N8	PA260-Z8	118	PA260-U5	96
30 x 36	PA336-N8	PA336-Z8	102	PA336-U5	80
	PA348-N8	PA348-Z8	114	PA348-U5	92
60	PA360-N8	PA360-Z8	126	PA360-U5	104
	PA448-N8	PA448-Z8	124	PA448-U5	102
36 x 48	PA460-N8	PA460-Z8	138	PA460-U5	116

Model AY - Ergonomic Height Platform

WxL (in)	8" Full Pneumatic Casters Cat. No.	8" Semi Pneumatic Casters Cat. No.	Wgt. (lbs)	5" Casters Cat. No.	
				Polyurethane	Wgt. (lbs)
24 x 48	AY248-N8	AY248-Z8	160	AY248-U7	140
30 x 60	AY360-N8	AY360-Z8	182	AY360-U7	162

Model AG - Pull Wagon

WxL (in)	Cat. No.'s			Wgt. (lbs)
	12" Pneumatic	16" Pneumatic	12" Mold On Rubber	
24 x 36	AG236-N2	AG236-N6	AG236-R2	96
	AG248-N2	AG248-N6	AG248-R2	112
30 x 60	AG360-N2	AG360-N6	AG360-R2	130
36 x 60	AG460-N2	AG460-N6	AG460-R2	136
	AG472-N2	AG472-N6	AG472-R2	148